### **VACUUM SEALER SU-310**

Tabletop model. 10 m<sup>3</sup>/h. 320 mm.





## Sales Description

320 mm. sealing bar. 10 m³/h Busch vacuum pump. Vacuum controlled by sensor.

- ✓ Powered by Busch.
- √ Vacuum controlled by sensor.
- √ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- √ Backlit touch keyboard.
- √ Programmable: 25-programme memory. Blocking option.
- √ "Pause" button.
- ✓ Phased vacuum programme.
- ✓ Detection of the evaporation of liquids.
- √ Double seal.
- √ Cordless sealing bar.
- √ Progressive decompression.
- $\checkmark$  Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber. Deep-drawn chamber.
- ✓ Damped transparent lid of high durability polycarbonate.
- ✓ Dry-oil programme for drying the pump.
- Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.
- √ NSF-listed model.

### INCLUDES

- √ Busch pump.
- ✓ Sensor controls.
- ✓ Programmable.
- √ Vacuum plus: up to 10 seconds of extra vacuum pull.
- ✓ Soft air function.
- ✓ Clear methacrylate lid.
- ✓ Pause function.
- ✓ Liquid detection system.
- ✓ Dry oil cycle.
- √ NSF approved.
- √ Filling plate.

### **OPTIONAL**

- Inert gas.
- Printer.
- Wireless connectivity.
- Vacuum packing bags.
- External vacuum kit for Vac-Norm, containers and accessories.
- Support for liquid packaging.
- Additional filling plates.

### Accessories

- □ Filling plates
- ☐ Liquid insert plates
- Vac-norm external vacuum kits
- Vac-norm containers
- Smooth bags for vacuum packing
- ☐ Trolley for vacuum packing
- machines
- ☐ Thermal labels for CG2 / RB printer
- □ RB desktop printer for SU vacuum packing machines
- ☐ Thermal transfer labels for RB printer

### **SPECIFICATIONS**

Pump capacity: 10 m<sup>3</sup>/h Pump capacity (60 Hz): 12 m<sup>3</sup>/h

Bar length: 320 mm Total loading: 370 W

Vacuum pressure (maximum): 2 mbar

### Internal dimensions

- √ Width: 330 mm
- ✓ Depth: 360 mm
- √ Height: 155 mm

### External dimensions (W x D x H)

- ✓ Width: 384 mm
- ✓ Depth: 465 mm
- ✓ Height: 403 mm

Noise level (1m.): 75 dB(A) Background noise: 32 dB(A)

### AVAILABLE MODELS

1140732	SU-310P 230/50-60/1
1140733	SU-310GP 230/50-60/1
1140737	SU-310P 120/50-60/1
1140738	SU-310GP 120/50-60/1
1140740	SU-310GP+ 120/60/1
1140727	SU-310GP 230/50-60/1 AUS
1141093	SU-310P 100/50-60/1

<sup>\*</sup> Ask for special versions availability







updated **15/03/202**4

product sheet

# FOOD PRESERVATION AND SOUS-VIDE

# updated 15/03/2024 product sheet





sammic | www.sammic.com Food Service Equiment Manufacturer

Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Item Qty		Project	Date
		Item	Qty